

**CENTER 122 RS-232 / DATALOGGER/ TRUE RMS AUTO RANGE MULTIMETER**

Center 120 is our standard DMM series and they all with IEC1010 1000V CAT III. In order not to cumbersome the out look when doing RS232 Communication we had specially designed interface to meet the requirement of regulation without big chunk of adaptor. This tester also equipped with super wide ranger for capacitor measuring. Both 122 have RS-232 interface and 122 is True RMS DMM and data logger

**FEATURES**

- Download data for analysis or monitoring the real time data through easy access “Slim Com” RS-232 connection.
- Led back light system for operation under poor illumination
- Shock absorbing holster add an extra protection and provide a built-in tilt stand.
- 32.000 Records datalogger (122)
- 1ms PEAK (Max/Min) Function



Display: 3-3/4 digital (4000 count) display  
 Sampling Rate: 2 times/sec (dig reading), 20 times/sec (analog bar indication)  
 Battery: 9V  
 Dimensions (With holster): 209x94x48 mm  
 Weight (With holster): 600g

**SPECIFICATIONS**

Function	Range	Resolution	Accuracy
DCV	400mV ~1000V	0.1mV ~1V	0.3% rdg + 2dgts
ACV	400mV ~750V	0.1mV ~1V	0.5% rdg + 5dgts
DCA	400µA ~20A	0.1µA ~0.01A	0.8% rdg + 2dgts
ACA	400µA ~20A	0.1µA ~0.01A	1% rdg + 5dgts
Ohms	400Ω ~ 40MΩ	0.1Ω ~ 10KΩ	0.3% rdg + 2dgts
	4nF ~ 40mF	1pF ~ 10pF	1.9% rdg + 20dgts
HZ(VA-HZ)	4KHz ~ 40 MHz	1Hz ~ 10 KHz	0.05% rdg + 1dgts
RPM	40k ~ 400 MRPM	0.01K ~100KRPM	0.05% rdg + 1dgts
Temp	-50 ~1000°C	1°C	1% rdg + 2°C
	-58 ~1832° C	1°F	1% rdg + 4°F
0 ~ 2V		Active Sound Level: ≤ 40Ω	

**Reference to order: JR 033,000,003**

Supplied with: points of evidence, the 9 V battery, case, converter temperature, K type temperature probe, cable connection to computer (RS232), software, rubber belt against shocks and manual.

**UNIT PRICE: € 330.00 + VAT**